

iTrans

Fully Automatic Loading And Unloading System



- » **Automatic Loading and Unloading**
Fully automated processing of loading and unloading, save time and manpower.
- » **Complete equipment delivery**
The complete equipment is put in the container for delivery, saving delivery costs.
- » **Flexible layout**
The loading module is suitable on both the left and the right, achieving flexible on-site layout methods.
- » **Fast Loading**
Continuous loading time reaches as short as 110 seconds.
- » **Automatic Sheets Splitting**
Lifting the corners of sheets first, avoids loading multiple sheets.
- » **Material Detection**
iTrans gives an intelligent reminder once no sheet detected on the material pallets.

Technical Parameters

Model:	P3	P4
Working area:	1000mm*1000mm-3000mm*1500mm	1000mm*1000mm-4000mm*2000mm
Module dimensions:	5400mm*3970mm*3070mm	9000mm*6000mm*4000mm
Weight:	6100kg	10000Kg/11000Kg
Continuous reloading time:	110s	150s/200s
Maximum thickness of feeding plate:	25mm	12mm/25mm
Maximum loading weight:	900Kg	800Kg/1600Kg
Finished product trolley maximum load:	3T	3T
Maximum height of finished sheet:	85mm	300mm
Operation method:	Touch screen operation	Touch screen operation

Version number 2021 11
(Above data is only for reference)